Elevators might take up little space in buildings. Still, they d`UmU'g][b] VWbhfc`Y`]b'U'Vi]X]b[g'YbYf[mWcbgi a dh]cb' UbX'WVb'VYbY hZfca `]a d`Ya Ybh]b[`a cfY`Y W]YbhUbX' WcghY YWAjjY'gmghYa g''

; UbbYth: Ya]b[g'j Yfh]W/ `ffUbgdcfhUh]cb hYUa incorporates sustainable design practices and energy conservation into vertical transportation projects. bZcfa YX XYVJg]cb!a U_]b[']b U``dfc YVI/d\UgYg'[i]XYg'h\Y` design team or building operator through implementing sustainable technologies.

< YfY UfY Zci f'k Ung ci f'j Yfh]WD HUbgdcfHUh]cb HYUa recommends incorporating sustainable elevator design practices.

1. Reduce Power Consumption with Machine-Room-Less Elevators

1

» FYXiWYXZcchdf]bhk]h\]bVi]`X]b["

BENEFITS OF MRL ELEVATORS

A F@hYVN.bc`c[mXY`]jYfg`\][\Yf`YbYf[mY V)[YbV1/mk]h\]b` h\Y`\c]ghkUm2fYgi`h]b[`]b.

- » Reduced electrical consumption.
- » @ckYf``]ZYVMWY`W¢ghg"
- » 9`]a]bUhYX bYYX Zcf cj Yf\YUX dYbh\ci gY' construction.
- » A]b]a]nYX`\YUh]b[`UbX`Wcc`]b[`fYei]fYa Ybhg"
- » Improved durability and maintainability eliminate the bYYX Zcfgc] # UHYf WtbHJa]bUhjb[\mXfUi `]W i]X"

DRAWBACKS OF MRL ELEVATORS

Unlike the commonly acceptable hydraulic and traction YYj Uhcf`ghUbXUfXgz̆g]n]b[`UbX`gdUWY`fYei]fYa Ybhg`X] Yf` Ua cb[`h\Y`j Uf]ci g`A F@a Ubi ZUWi fYfg"

- » J Uf]ci g`\c]głk Umd`Ubg'UbX'Y'Yj Uh]cb Zcchdf]bhg'a U_Y' it challenging to provide a design that enables the dUfh]WjdUh]cb cZYUW\ A F@Y'Yj Uhcf'a Ubi ZJWh fYf"
- » MRL technology can be highly proprietary, resulting]b U ZcfWYX `cb[!hYfa `fY`Uh]cbg\]d Zcf`dfYj Ybh]j Y a U]bhYbUbWY VYhk YYb h\Y ck bYf UbX A F@Y`Yj Uhcf` a Ubi ZJMi fYf"
- » Customizing elevator designs is limited to a a Ubi ZUM/i fYfg'gHUbXUfX'cdh]cbg'Zcf'Wff'YbWcgi fYgž' YbhfUbWfgžUbX'cdYfUh]b[#g][bU'' | hi fYg''

2. Be Wary of Leaky Hydraulic Elevators

<nXfUi `]WY`Yj Uhcfg'di a d`\nXfUi `]W i]X`hc'U'Wh]bXYf# plunger assembly that vertically moves the piston that fU]gYg'h\Y'Y`Yj Uhcf'WV'UbX``ck Yfg']h'VUW_'Xck b"'H\Y` V&bj Ybh]cbU`'Wh]bXYf#d`i b[Yf'UggYa V`mfYg]XYg']b'U'k Y``` hole directly beneath the elevator.

NYUfgʻU[cžh\YgYʻUggYaV`]YgʻkYfY`]bghU``YX`k]h\``]hh`Ycf bc`dfchYVMjcb`Zfca`h\Y`giVgifZUWY`Y`YaYbhg''K]h\cih h\Y`UV]`]hmhc`]bgdYVMih\Y`UggYaV`mVYbYUh\`h\Y`gifZUWYž XUaU[Y`hc`h\Y`Wh]bXYf`h\Uhkci`X`fYgi`h]b`U`\mXfUi`]W i]X``YU_Wti`X`[c`i bbch]WYX''H\YWtbgYei YbWgWti`X` VY`gc]`UbX`[fci bXk UhYfWtbHJa]bUh]cb'': cfh bUhY`mž leaks have become less common as these elevators are replaced or modernized.

A maintenance contract does not cover the hydraulic `YU_`fYdU]f"'H\Y'Wn]bXYf#d`i b[Yf'UggYa V`mWcghž]bWl X]b[` H\Y`fYei]fYX`fYa YX]Uh]cb`cZWcbHJa]bUbhgžWlb`fUb[Y`]g``cWIHYX`Uh'U``ck Yf``Yj Y`"`5`VUgYa Ybhfcca `Wb`VY`Ub` cdh]cb`k \Yb`UfccZa ci bHYX`a UW\]bY`fcca `]g`]a dcgg]V`Y` cf`bchXYg]fYX"'HfUWIjcb`Y`Yj Uhcfg'h\Uh'UfY`bchA F@\Uj Y` larger capacities available. In certain applications, it is YUg]Yf`hc`Wcbhfc``h\Y`a UW\]bY`Ybj]fcba Ybhk]h\`h\Y` machine located in a separate machine room than in the \c]ghk Um'

About the Author

Hcbm8YZfUbWrgWt]gH\YJ]WrDfYg]XYbh/ DfUWf]Wr8]fYWrcfžJYfh]WD HfUbgdcfhUh]cbUh; UbbYth: Ya]b["HcbmWUbVYfYUW\YXUh UXYZfUbWrgWt4[ZbYHWta].

About the Article

 $H\ [g'Ufh]WY\ k\ Ug'k\ f]HYb\ Zcf\ h\ Y\ cb\]bY\ \underline{:\ UbbYH:\ Ya\ [b[\ BG\ ;\ <HG\ :\ }}$

4